

BSS Case for ATEM Mini

The BSS case is an "all in one" live streaming video system in the stable hard case. Each execution includes a 10", full HD field monitor, an integrated power supply, a fan, as well as all connecting cables and small parts for installing an ATEM Mini PRO or ATEM Mini Pro ISO video mixer.

BSS Case Economic

Consistently inexpensive and yet everything is included. This is the best way to describe the economic case for the ATEM Mini. With the integrated FullHD monitor, it meets all the requirements of a director's screen and your ATEM Mini is well protected in the sturdy case and ready for immediate use.

BSS Case Basic

The basic case includes all connections of the ATEM Mini Pro / ISO with audio and headphone connection in 3.5mm jack design. All connections are routed to the outside on the back and left side of the case.

BSS Case Professional

In the Professional Case, the audio connections¹ are designed as XLR sockets with a cable from Sommer Cable and a lockable 6.35 mm jack socket is installed as a headphone connection. In addition, connection sockets from Neutrik are installed. The fan speed is thermostat controlled.

BSS-Case Professional SDI

Contains the features of the Case Professional and is designed with its BNC connection sockets on the ATEM SDI. Optional functions can be configured for all versions. (Option)



Case shown with optional ATEM Mini

	BSS-Case Economic	BSS-Case Basic	BSS-Case Professional	BSS-Case SDI
ATEM Mini Pro (ISO)	Option	Option	Option	Option
10" Full HD-Monitor	✓	✗	✗	✗
10" HD-Broadcast Monitor	✗	✓	✓	✓
Integrated power supply 5A	✓	✓	✓	✓
Fan - continuous operation	✓	✓	✗	✗
3.5mm audio jacks	✓	✓	✗	✗
3.5 mm - headphone jack	✓	✓	✗	✗
Fan - thermostat controlled ²	✗	✗	✓	✓
XLR - audio jacks	✗	✗	✓	✓
Socket version Neutrik ³	✗	✗	✓	✓
3.5 mm - headphone jack	Option	✓	✗	✗
6.35 mm - headphone jack	✗	Option	✓	✓
2 x 3G-SDI converters ^{4,5}	✗	✗	Option	✗
1 x 3G-HDMI converter ⁴	✗	✗	✗	Option
3/8 inch threaded socket	✗	Option	Option	Option
USB charging socket	✗	Option	Option	Option
12V battery connection	✗	Option	Option	Option

All order parameters can be found in our shop at: <https://bss-streamingservice.de/en/shop-2/>

¹ Regardless of their technical design, the audio connections on the BSS case correspond to those of the ATEM Mini: 2 x unbalanced stereo inputs

² Pulse width modulated speed control - whisper quiet operation

³ The HDMI, Ethernet, XLR and jack sockets are components from Neutrik AG

⁴ HDMI-SDI or SDI-HDMI Micro Converter from Blackmagic Design Ltd.

⁵ With this option, the case is only available ready-to-use with the ATEM Mini Pro / ISO installed due to the compact space available.

Technical specifications

Commissioning conditions

Temperature range	+5° – +40° C	
Relative humidity	20 – 90%	Not condensing
Storage temperature	-20° – +60° C	
Do not use at altitudes over 2000m above sea level		
Do not operate in a dusty environment		

Electrical connection data

Supply voltage	~230V/5A
Power	60 W

Height and weight

L x W x H	430 x 380 x 154 mm
approx. weight (varies depending on equipment)	3,1 kg (Economic)
	3,7 kg (Basic)
	4,2 kg (Professional / SDI)

Delivery condition / scope of delivery

For non-ATEM Mini Pro/ISO/SDI versions, all hardware to install one is included. The installation is carried out by the customer.

The versions including the installed ATEM Mini Pro/ISO/SDI are supplied ready for use.

1 x BSS-Case	
1 x Power cord 1,80 m	with safety plug (CEE 7/7)
2 x 0,7 m Audio adapter cable*	3.5 mm stereo jack - 3-pin XLR male

*only with BSS Case Professional / Professional SDI

BSS Streaming Service
Mühlstraße 80
D-73655 Plüderhausen
Germany

<https://bss-streamingservice.de/en/bss-cases-for-atem-mini/>



BSS Case Basic front side



BSS Case Basic right side



BSS Case Basic left side



BSS Case Basic reverse side



BSS Case Professional reverse side



BSS Case Professional SDI reverse side

Technical changes reserved.