

BSS case for Rodecaster Video

The BSS case is an “all-in-one” live streaming video system in a

- sturdy hard case.
- with an integrated 16.1", full HD monitor
- an integrated power supply unit, a PWM-controlled fan¹
- high-quality connection sockets²
- as well as all connection cables and small parts for installing a
- Rodecaster video mixer.
- further options such as battery connection for operation with 12V and as an uninterruptible power supply can also be configured

All Rodecaster Video connections are located on the case. For the integrated MicroSD card slot there is a holder for self-installation of an external reader³. With the integrated FullHD monitor, it meets all the requirements of a control room monitor and the Rodecaster Video is well protected and ready for immediate use in the sturdy case.

Additional optional functions can also be configured. (option)



Photo shows case with optional Rodecaster video

BSS-Case Rodecaster Video	Components
Rodecaster Video (video mixer)	Option
16,1" Full HD-Monitor	✓
Integrated power supply unit 6.67 A	✓
Fan - PWM thermostat controlled	✓
Lockable combo audio sockets	✓
Lockable 6.35 mm audio sockets	✓
Neutrik socket version	✓
2 x 3G-SDI converter	Option
USB charging socket	Option
powerCON® Power connector ⁴	Option
12V battery connection	Option

⁴powerCON is a registered trademark of Neutrik AG

¹ Pulse-width modulated control = whisper-quiet operation

² The HDMI, Ethernet, XLR and jack sockets are components from Neutrik AG

³ An external micro SD card reader is not integrated for technical reasons. However, a corresponding recess in the cover plate with a holder is provided for this purpose. Please refer to our support article "[SD card slot in the Rodecaster case](https://bss.streaming-service.de)" in our technology blog at <https://bss.streaming-service.de>

Technical data

Commissioning conditions

Temperature range	+5° – +40° C	
Relative humidity	20 – 90%	Non-condensing
Storage temperature	-20° – +60° C	

Do not use at altitudes above
2000m above sea level

Do not operate in dusty
environments

Electrical connection values

Supply voltage	~230V/6,67A
Power	80 W

Size and weight

L x B x H	430 x 380 x 154 mm
Approx. weight (varies depending on equipment)	8.3 kg (Basic) up to 9.5 kg

Delivery condition / scope of delivery

For the versions without Rodecaster Video, all hardware parts for the installation of a Rodecaster Video are included. Installation is carried out by the customer. The versions including mounted Rodecaster Video are supplied ready for installation.

1 x BSS-Case	
1 x mains connection cable 1.80 m	with Schuko plug (CEE 7/7)
<i>With option powerCON® True1</i>	
1 x mains connection cable 1.50 m	with Schuko plug and powerCON® True1

BSS Streaming Service
Mühlstraße 80
D-73655 Plüderhausen

<https://bss-streamingservice.de/>



BSS-Case Rodecaster front side



BSS-Case Rodecaster right side



BSS-Case Rodecaster left side



BSS-Case Rodecaster backside



BSS-Case Rodecaster backside & USB



BSS-Case Rodecaster backside & SDI

Technische Änderungen vorbehalten.